



Simulation, Generation, and Characterization of a High Brightness Electron Source

Presented by

T. Srinivasan-Rao,

Brookhaven National Laboratory, Upton, NY 11973

Future Light Sources Workshop, Argonne, IL, April 6-9, 1999

Collaborators


- T. Srinivasan-Rao, J. Schill, I. Ben-Zvi, BNL
- K. Batchelor, J. P. Farrell, Brookhaven Technology Group, Inc.
- J. Smedley, State University of New York, Stony Brook
- X. E. Lin, A. Odian, SLAC

Simulations

- **Used MAFIA and PEGUNGS**
- **1 MV across 1 mm gap, .25 mm emitting spot, .5 mm anode hole**
- **Emittance as a function of current and pulse duration**
- **Investigated effect of a 1 eV random initial energy**
 - **Contributes $.17 \pi$ mm-mrad to total emittance**
- **Total beam emittance of $.39 \pi$ mm-mrad for 100A, 10ps bunch**
- **Longitudinal energy spread of 0.15% for 100A, 10ps bunch**
- **Investigated effect of curving the cathode to provide collimation or beam waist**

Geometry for Simulation

- 1 mm gap
- .5 mm radius anode hole
- .25 mm emitting spot, uniform current density
- 1 MV potential, 1 GV/m gradient




Current	Charge	Bunch length	Emittance	Brightness
A	nC	ps	π mm mrad	$\frac{A}{(mm - mrad)^2}$
100	1	10	0.16734	3571
100	0.3	3	0.0882	12854
100	0.1	1	0.062	26014
100	0.03	0.3	0.0728	18868
500	0.5	1	0.207	11668
250	0.25	1	0.132	14348
50	0.05	1	0.0386	33557
10	0.01	1	0.0446	5027

Thermal and Space Charge Contributions

Current	Charge	Initial Energy	Emittance
A	nC	eV	π mm mrad
100	1	0	0.251
100	1	1	0.287
100	1	10	0.597
100	1	100	1.704
10	0.1	0	0.023
10	0.1	1	0.171
10	0.1	10	0.530
10	0.1	100	1.682


Transverse Phase Space

1 nC in 10 ps (100 A)




Measurements

- **Experimental Arrangement**
- **Pulser provides 1 ns voltage pulse with 100ps rise and fall**
- **Dark Current**
 - **10 pC at 650 MV/m**
 - **Fowler-Nordheim plot gives $\beta = 30$ for a well conditioned surface**
- **Photoemission using KrF excimer**
 - **Charge has a linear dependence on laser energy**
 - **Field dependence**




Voltage Trace from MV pulser

1 ns duration, with 100 ps rise and fall




Experimental Arrangement



- Variable electrode spacing

- Faraday cup with mirror surface

Fowler-Nordheim Plot for Cu Cathodes



Field Dependence of Extracted Charge

- Investigated the dependence of extracted charge on applied voltage for a constant laser energy.

- For small values of $(h\nu - \phi)$,


$$Q \propto \left(h\nu - \phi + \sqrt{\frac{e\beta E}{4\pi\epsilon_0}} \right)^2$$

- Plot $Q^{1/2}$ vs $E^{1/2}$

$$\frac{\text{slope}}{\text{intercept}} = (h\nu - \phi)^{-1} \sqrt{\frac{e\beta}{4\pi\epsilon_0}}$$

- Yields $\beta = 5$ for $\phi = 4.65 \text{ eV}$

Sqrt E vs Sqrt Q



Conclusions and Future Plans

- Simulations show that a pulsed power gun with a 1 GV/m gradient should be able to provide a 1 nC beam in 10 ps with
 - Total emittance of $.39 \pi$ mm-mrad
 - Energy spread of 0.15%
 - Even better values of total emittance may be possible for shorter pulse durations
- It is possible for a copper cathode to support a field of 1 GV/m without breakdown
- The field enhancement factor for photoemission is lower than than the field enhancement factor for field emission
- Future plans include photoemission with 4th harmonic of NdYAG, measurements of beam emittance and energy spread, and an eventual upgrade to 5MeV