

# Undulator Vacuum

*Ulrich Hahn, HASYLAB at DESY*

8. 11. 1999

*Outline*

Introduction

Undulator Vacuumchambers

Structure of the Vacuumchambers

Chamber Alignment

Pressure Distribution

*People involved at DESY:*

N. v. Bargen  
J. Brehling  
C. Boudou  
S. Greulich  
U. Hahn  
D. Hubert


T. Kamps  
R. Lorenz  
G. Marquart  
M. Meschkat  
J. Pflüger  
M. Rüter

H. Schlarb  
G. Schmidt  
H. Schultz  
A. Swiderski  
H. Thom  
S. Vilcins

H. – P. Wedekind  
M. Wendt  
M. Werner  
K. Wittenburg  
K. Zapfe – Dueren

*at APS – ANL:*

P. DenHartog, M. Erdmann, E. Gluskin, E. Trakhtenberg, G. Wiemerslage, S. Xu  
*J. Noonan et. al.*



4 diagnostic blocks

beam

3 undulator sections  
(magnet structure + vacuum chamber)

## The Undulator Vacuum System

**length:** ~ 15m,  $\varnothing$  9.5 mm

*vacuum:* outgassing rate  $< 1 \cdot 10^{-11} \text{ mbar} \cdot \text{l/sec} \cdot \text{cm}^{-2}$

*particle free:* according TESLA specification

**4 monitor blocks (185 mm long)**

*monitoring of the particle beam position in front and at the end of the 3 undulator modules*

**3 FEL - vacuum chambers 4.5m long 128x11.5mm<sup>2</sup>**

*monitoring of the particle beam position in the gap of the undulator modules*

*steering of the particle beam in the gap of the undulator modules*



## VACUUM CHAMBER DESIGN

There are several design criteria for the undulator vacuum chamber:


- The undulator gap size is 12 mm
- The chamber has to permit beam position measurement and steering in the gap
- The chamber has to be vertical and horizontal aligned within 0.1mm
- Low electrical resistance and small micro-roughness of the inner beampipe are needed to minimize resistive wall and wake field effects on the beam
- Two types of beam position monitors
- Pick up monitors (chamber 1 and 2) danger of sparking for short bunches
- Waveguide monitor (chamber 3) no risk of sparking → TTF phase II

# BEAMPOSITION MONITORS

Pick up monitors (chamber 1 and 2) (M. Wendt et. al)  
*danger of sparking for short bunches*





Waveguide monitor (chamber 3) (R. Lorenz et. al)  
*no risk of sparking → TTF phase II*



# FEL vacuum chamber

designed and manufactured  
by DESY-HASYLAB and APS-Argonne National Lab  
Chicago





Teikam

RESULTS: 3 B.C. 1, STRESS\_3, LOAD SET 1


STRESS - VON MISES MIN: 1.61E+00 MAX: 1.00E+05

DEFORMATION: 1- B.C. 1, DISPLACEMENT\_1, LOAD SET 1

DISPLACEMENT - MAG MIN: 0.00E+00 MAX: 2.13E+00

FRAME OF REF: PART

VALUE OPTION: ACTUAL



/home/rueter/ideas\_work/ideas\_light/kammeraufhaengung.mf1

RESULTS: 3- B.C. 1, STRESS\_3, LOAD SET 1


STRESS - VON MISES MIN: 6.63E-02 MAX: 6.76E+02


DEFORMATION: 1- B.C. 1, DISPLACEMENT\_1, LOAD SET 1

DISPLACEMENT - MAG MIN: 0.00E+00 MAX: 7.55E-03


FRAME OF REF: PART


VALUE OPTION: ACTUAL














12/30/1999


102.2

ACHTUNG  
STARKES MAGNETFELD










## Horizontal Offset of the Undulatorchamber



/home/rueter/ideas\_work/ideas\_light/FE-udkam-Biegung.mf1

RESULTS: 3- B.C. 1,STRESS\_3,LOAD SET 1  
STRESS - VON MISES MIN: 2.66E-08 MAX: 3.52E+04  
DEFORMATION: 1- B.C. 1,DISPLACEMENT\_1,LOAD SET 1  
DISPLACEMENT - MAG MIN: 0.00E+00 MAX: 5.75E+00  
FRAME OF REF: PART

VALUE OPTION:ACTUAL  
SHELL SURFACE: TOP






Diagramm f. Lage u Hoehenänderg






Lageabweichungen Kollimator und Undulator, neigungsreduziert



Höhenabweichungen Kollimator und Undulator








## Pressure distribution of a 5m long vacuum pipe

pumping speed at 0m: 0.5 l/sec, outgassing rate:  $10^{-12}$ mbar\*l/(sec\*cm<sup>2</sup>)  
pipe diameter: 9.5 mm - conductance C: 0.02l/sec



$$P(x) = a \cdot u \cdot \left[ \frac{L}{S} + \frac{x}{C} - \frac{x^2}{2 \cdot C \cdot L} \right]$$