


# Design Considerations for the LCLS

C.Limborg, SLAC

- Small slice emittance production
- Coherent Synchrotron Radiation
- Undulator
- Resistive wall wakefield

# SASE FELs



## SASE FEL

- Starts from Noise from spontaneous emission
- Exponential growth of radiated power
- Saturation level

Theory well developed and verified by simulations






XFEL  $\rightarrow$  0.1 nm

(or 1 Å)


Just 2 years ago:  
SASE saturation not yet demonstrated

Since September 2000:  
3 SASE FEL's demonstrate saturation



# X-Ray SASE requirements

## The LCLS (Linac Coherent Light Source)





$$\epsilon_{n,slice} \sim 1.2 \text{ mm.mrad}$$

$$I_{pk} = 3.4 \text{ kA (230fs, 1nC)}$$

$$\sigma_{\delta} < 5 \cdot 10^{-4}, 14.3 \text{ GeV}$$

**Saturation of 1.5 Å, undulator ~100m**

# Photo-injector Beamline



1nC  
 low  $\epsilon_{thermal}$   
 120MV/m  
 120Hz



# Photo-injector Simulations

## Tuning with **Homdyn** then **PARMELA**

✓  $\epsilon_{th} = 0.5$  mm.mrad


✓ Pulse 10 ps but 0.7 ps rise time

✓ Stability, flexibility of beamline,  
PARMELA vs experiment [C.Limborg, WE-P-14]




# GTF Summer 2002

Spectrometer Image  
of Slice Quad Scan Data



Instantaneous  
Peak Current

Slice Emittances



$\epsilon_{\text{slice}} = 1.3 \text{ mm.mrad}$   
for 130 A  
 $\sim$  very close to  
LCLS requirements

Similar  
measurements at the  
DUVFEL facility  
(Spring 2002)



Courtesy D.Dowell [WE-P-07 Dowell et al.]

# Sumitomo Spring 2002

1nC

$\epsilon_p = 1.2 \text{ mm.mrad}$

with "LCLS type" Gun




Frequency domain pulse shaping

Courtesy of J. Yang FESTA

Sumitomo Heavy Industries, Ltd.




# LCLS Linac Parameters for a 1.5-Å FEL




Two stages of bunch compression

1-nC, 10 ps with  $\varepsilon \sim 1.0$  mm.mrad  $\Rightarrow$  compressed and accelerated  
while preserving slice emittance, providing small energy spread  
 and stable operation

# Magnetic Bunch Compression





# Evolution Longitudinal Phase Space



courtesy P.Emma

# Coherent Synchrotron Radiation (CSR)


- Powerful radiation generates energy spread in bends
- Projected emittance growth (short bunch worse)



- Micro-bunching Instability: deteriorates  $\varepsilon_{\text{slice}}$  and  $\sigma_{\delta, \text{slice}}$   
Amplification of strongest line/energy density components  
First observed by M.Borland in simulations

# CSR Microbunching: theory / tracking

Microbunching Gain



(\*)S. Heifets et al., SLAC-PUB-9165,03-2002  
E. Saldin et al., Jan. 02, NIM, A483,2002  
Z. Huang et al., April 02, PRST-AB, 07-2002

Z.Huang WE-O-04


Initial modulation wavelength prior to compressor

# Minimizing Microbunching


Without Super-Conducting Wiggler  
 $\sigma_\delta = 3 \cdot 10^{-6}$  before BC2




energy profile



long. space



temporal profile




Entrance of undulator


With Super-Conducting Wiggler  
 $\sigma_\delta = 3 \cdot 10^{-5}$  before BC2




energy profile



long. space




temporal profile



# Undulator

- 120 m undulator channel
  - ✓ 33 segments of 3.4 m,  $\lambda_u = 3$  cm,  $K = 3.71$
  - ✓ space for future enhancements (seeding, slicing, harmonics)
- 3.4-m section already built at ANL and is being measured



Al temperature-compensation plate

Titanium strong-back

Va permendur poles


Nd-Fe-B magnets

Advanced  
Photon  
Source



Courtesy E. Gluskin, L. Moog, ANL

# Undulator Systems



➡ Trajectory straight  $\Rightarrow \sigma_{x,y} < 5\ \mu\text{m}$  over gain length

## Beam-based Alignment

- ✓ Measure Energy dependent trajectory
- ✓ Move Quadrupoles and undulators,
- ✓ Correct BPM offsets

$\sigma_{x,y} < 3\ \mu\text{m}$  achievable along undulator

P.Emma Simulations





# Undulator Chamber Wakefields

- Resistive wall dominant over roughness and geometric wakefields
- $h_{1/2, \text{chamber}} = 2.5 \text{ mm}$  for high undulator fields

$$\left(\frac{\sigma_E}{E}\right)_{RW} \approx (0.22) \frac{e^2 c N L_u}{\pi^2 r E \sigma_z^{3/2}} \sqrt{\frac{Z_0}{\sigma}}$$


Wake changes 'slice' energy during exponential gain regime



S. Reiche, [WE-P-49] Active pulse length control down to 10 fs by wakefields

# Peak Power along Undulator

Start-to-End Simulations: PARMELA  $\Rightarrow$  Elegant  $\Rightarrow$  Genesis



~40% power loss due to wakefield

Courtesy S.Reiche

# Project Schedule

2003 – Project Engineering Design Begins  
Spring 2004 – Complete Preliminary Design  
October 2004 – Start long-lead procurements  
October 2005 - Start of civil construction  
Winter 2007 – Begin FEL commissioning  
October 2008 – Project Complete

# Conclusion

Many challenges

- ❖ Very promising photo-injector results
- ❖ CSR : good understanding
- ❖ Resistive wall wakefields in undulator

<http://www-ssrl.slac.stanford.edu/lcls/CDR/>



X-Ray optics

R.Bionta WS-P-09

Short Electron bunches

P.Krejcik TU-O-08

Short X-Ray Pulses

J.Hastings WS-O-11

# Back-Up

